

12" LED SURFACE MOUNT DOWNLIGHT

PF-SM12R-LED-25W-30K-WH








DESCRIPTION

12" LED Ultra-Slim Downlight features Edge-lit technology to produce a smooth, uniform and reduced-glare lighting effect. An affordable alternative to air-seal IC recessed housing or fire-rated boxes. Driver-On-Board technology eliminates the demand for traditonal LED driver and still dims with industry standard TRIAC / ELV dimmers. Suitable for dry, damp, or wet locations.

ADDITIONA INFORMATION

Compatibility: installs into standard J-box applications



SPECIFICATIONS

| PF-SM12R-LED-25W-30K-WH |
|----------------------------|
| WHITE |
| BLACK, BRUSHED NICKEL, ORB |
| EDGE-LIT |
| POLYCARBONATE |
| POLYSTYRENE |
| |

PRIMARY LIGHTING

| 25W LED |
|------------|
| 1700 LM |
| INTEGRATED |
| 120V |
| 3000K |
| 90 |
| |

DIMENSIONS

| DIAMETER | 12" | |
|-----------|---------|--|
| HEIGHT | 0.94" | |
| WEIGHT | 2.3 LBS | |
| EXTENSION | N/A | |
| BACKPLATE | N/A | |



Prottofos Corporation www.prottofos.com