



PF-EM-104-DLW-WH













DESCRIPTION

The dual-head emergency light is made with injection-molded thermoplastic ABS housing with a 5VA flame rating. Innovative, easy installation in minutes and is suitable for wall mount applications. Universal J-box mounting pattern. (2) 12 SMD 2835 LED lamp heads for emergency mode. Test switch and charge indicator are included. UL certified. Rated for indoor / damp locations. Outdoor / wet location option available.

ADDITIONAL INFORMATION

Built-in 3.6V 700mAh Nickel cadmium battery. Test switch and charge rate included.

EM RUNTIME: >90 Minutes **EM RECHARGE:** 24 Hours

SPECIFICATIONS

SKU	PF-EM-104-DLW-WH
FINISH	WHITE
OTHER FINISHES	CUSTOM
COLLECTION	EMERGENCY
MATERIAL	ABS
DIFFUSER	CLEAR

PRIMARY LIGHTING

LIGHT SOURCE	(2) 1.2W LED
LUMENS	OUTPUT 200 LM
# OF BULBS	INTEGRATED
VOLTAGE	120V - 277V
COLOR TEMP	N/A
CRI	N/A

DIMENSIONS

WIDTH	9.82"
HEIGHT	4.13"
WEIGHT	1.0 LBS
EXTENSION	2.69"
BACKPLATE	N/A