

PF-TL-120-30K



DESCRIPTION

This field cuttable LED Strip Tape is an ideal solution for accent lighting in residential, commercial and retail applications. The 120V AC LED Strip Tape can be easily installed without the need of any additional driver, in indoor and outdoor applications.

SPECIFICATIONS

Electrical	Input Voltage	120V AC
	Power Consumption	4 W/Ft (10 W/M)
Specs	Color Temperature	3000K
	Lumen Output	300Lm/Ft (984Lm/m)
	CRI	90+
	Dimmable	Yes, with TRIAC dimmers
LED	Type	SMD2835
	Life Span	30,000 Hours
	Spacing	N/A
	# Per Foot	18 LEDs
Design	Dimensions (Inches)	0.79" W
	Dimensions (Millimeters)	20 mm W
	Max Single Run Length	50M (164Ft)
	Cut Length	Cuttable every 10CM (4")
	IP Rating	IP65
	Approved Location	Indoor/Outdoor w/ approved outdoor aluminum channel
Warranty	2 Years	
Approvals	cETLus	



FEATURES

FIELD CUTTABLE; 120V AC INPUT VOLTAGE

HIGH LIGHT EFFICIENCY, HIGH PF AND HIGH LUMENS

CONSTANT CURRENT DESIGN, OVERVOLTAGE PROTECTION

DROP CURRENT WHEN OVER TEMPERATURE TO PROTECT PRODUCT

DIMMABLE: TRIAC

NO NEED OF A TRANSFORMER BOX TO CHANGE AC TO DC

AMBIENT WORKING TEMPERATURE: -20 ~ 42°C (-4 ~ 107°F)

IP65 PVC EXTRUSION PROCESS

MIN. SECTION 4 INCH; MAX RUN 164FT

BARED POWER CORDS ON ONE SIDE, IT'S MORE CONVENIENT FOR CONNECTING

ETL CERTIFIED

2-YEAR WARRANTY FOR INDOOR/OUTDOOR USE

APPLICATIONS

BUILDING OUTLINES

SIGNAGE

DECKS

ARCHITECTURAL FEATURES

ACCESSORIES



PF-120V-EC

End Cap
(Indoor/Outdoor)



PF-120V-EXT

4Ft Aluminum
Extrusion



PF-120V-PC

8Ft Power Cord



PF-120V-PC-PL

5Ft Power Cord
with Plug



PF-120V-JC-6IN

Jumper, 6"



PF-120V-MC

Mounting Clips



PF-120V-ALP2208

Surface Mount
Extrusion & PC Cover

PF-120V-JC-1FT

Jumper, 1Ft

PF-120V-JC-3FT

Jumper, 3Ft

PF-120V-JC-6FT

Jumper, 6Ft



Protofos Corporation
www.protofos.com

11350 Old Roswell Rd, Ste 1100, Alpharetta, GA 30009
Information contained here is subject to change without notice